

EASY TO FOLD CONVEYOR:



The 4 m conveyor folds easily for transport.



The conveyor height is adjusted with a hand operated self-locking winch.



A strong quick release latch locks for safe transport.



With the conveyors folded the machine is compact for transport and storage.

OPTIONAL EXTRAS:



With the standard blade the wood can be split into 2 or 4 pieces.

A 6 part blade is an option.
The blades have a patented quick connection.



Hydraulically adjustable splitting blade.



Hydraulic log lifter.



Log table with hydraulic feeder.



The hydraulic log lifter folds behind the machine for transport.

TECHNICAL SPECIFICATION:



| | |
|-------------------------------------|-----------------------------|
| Power demand | |
| - standard model | 7,5 kW |
| - Easy model | 10 kW |
| Output, bulk m³/h | approx. 7-10 m ³ |
| Cross-cut sawbar | 0,325"/64 drive links |
| Sawbar | 15" |
| Splitting cylinder | ø 63 mm/5,5 t |
| - optional | ø 70 mm/7,0 t |
| Max. diameter of wood | ø 370 mm |
| Length of the wood | 200 mm...600 mm |
| Splitting speed | |
| - high speed | 2,8 sec |
| - high power | 4,2 sec |

| | |
|--|---|
| Splitting blade | |
| - optional | a blade that splits into 2 or 4 pieces a blade that splits into 6 pieces |
| Hydraulic pressure | 180 bar/60 bar |
| Flow of hydraulic pump | 44 l/min., 17 l/min. |
| Volume of the oil tank | 40 l/the oil is included as standard |
| Weight of the machine | |
| - machine and discharge conveyor | 590 kg |
| - machine+discharge conveyor+feed conveyor | 695 kg |
| Dimensions in transport position | |
| - height | 2520 mm |
| - width | 2450 mm |
| - depth | 1050 mm |
| Length of conveyor in work position | 4,0 m |
| Length of feed conveyor | 2,2 m |
| Optional power sources | tractor, electric motor or combustion engine |

Manufacturer:

MAASELÄN KONE OY

85800 HAAPAJÄRVI, FINLAND
tel. +358 8 772 7300, fax +358 8 772 7320
www.maaselankone.fi

Importer:

HAKKI PILKE 37



FIREWOOD
FASTER
SAFER
EASIER

WWW.MAASELANKONE.FI

MACHINE MODELS:



STANDARD MACHINE WITH FEED CONVEYOR

The feed conveyor carries the log into the machine. Machine operation is by the hand lever.



Maximum log diameter 37 cm. Splitting force 5,5 T. A 7, 0 T splitting cylinder is optional.



The spring-loaded support roller automatically opens the guard.



After splitting the firewood passes over a grid through which wood waste and splinters can fall.



Splitting speed is regulated automatically. Small logs - high speed. Large logs - slow, powerful movement.



Ergonomically correct working position: cutting with the right hand. Cutting and splitting takes place in a fully guarded area.



Blade height adjustment is quick and easy.



Automatic oiling of the cutting chain. Oil goes to the chain only when the machine is in use. There are separate tanks for the chain oil and hydraulic oil.



Triggering the splitting movement by foot.



EASYMODEL



The slightly inclined infeed conveyor keeps twisted wood on the table.



The sawbar cover is opened using a spanner. This allows easy access for maintenance.



EASY TO USE JOY STICK CONTROLS (OPTIONAL)

All functions of the machine are operated hydraulically: log feed, cross-cutting and height adjustment of the splitting blade.

