

Norwood Saw Mill Technical Data

	LumberMate® 2000 Full-Size Band Sawmill	LumberLite® 24 Mid-Size Band Sawmill
--	---	--

Maximum Cutting Capacities

Log Diameter (Maximum)	31" (77.5 cm)	24" (60 cm)
Board Width (Maximum)	24" (60 cm)	17" (42.5 cm)
Log Length (Maximum) (Standard before extensions)	13' (3.9 m)	12' (3.6 m)

Power Selections

Power Selections	<ul style="list-style-type: none"> ● 13hp OHV Honda GX ● 15hp OHV Kohler Command Pro ● 23hp OHV Briggs Vanguard V-Twin 	<ul style="list-style-type: none"> ● 8hp (305cc) OHV Briggs ● 9hp OHV Honda GX ● 13hp OHV Honda GX
-------------------------	---	---

Weight & Dimensions

Bed Length (Standard without optional bed extensions)	16' (4.8 m)	16' (4.8 m)
Width (At widest point on sawhead)	6'0" (1.8 m)	6'0" (1.8 m)
Weight (With heaviest power selection & no options)	1,053 lbs. (479 kg)	550 lbs. (250 kg)
Blade	1½" x 0.042" x 144" (3.125cm x 0.105cm x 3.6m) (1½" x 0.042" x 144" Optional)	1½" x 0.042" x 144" (3.125cm x 0.105cm x 3.6m)
Bandwheels	19" (47.5 cm)	19" (47.5 cm)
Drive	Centrifugal clutch	Centrifugal clutch
Set Display	8/4", 4/4", ¾" & standard scale (9/4", 6/4", 5/4" & 9/8" optional) (5cm, 4cm, 2cm metric scale optional)	8/4", 4/4", ¾" and standard scale

Optional Attachments & Equipment

Bed Extensions	● 4' (1.2m) & 2' (0.6m) sections	● 4' (1.2) msections
Trailer Package	●	
Toe Boards	●	
Lap Siding/Shingle Making Package	●	●
Cam Dogs	●	
Log Loader	●	
Leveling Feet	●	
Support Legs	●	
1½" Blade System	●	
Saw Carriage Cover	●	●
Stainless Steel Cross Bunk Covers	●	
Special Scales	● 9/4", 6/4", 5/4" and 9/8" 5cm, 4cm, 2cm metric	
Bar Oiler Kit		

