

Fransgård RV-Combi Rakes



RV-300
RV-390

Simple, strong combi-rakes, available in 2 sizes. These hayflays can work in many different crops for both tedding and raking. The hayfly can also be used for raking existing swaths into one large fluffy swath.

Fransgård



With the rear crop guards out of the way, the crop can be wide spread evenly.



When raking crops, the swath guards form a high, even and fluffy swath. 2 wheels under each rotor on the RV-390 allow cleaner raking on uneven ground.



The tines are lowered into working position by centrifugal force. They can be set for raking or tedding without the use of any tools. The rotor is designed to be solid and robust for a longer service life.



The working height is adjusted by pin holes over the gearboxes and can be fine tuned by the toplinek. The RV-390 is supplied with 4 ground wheels, optional extra for the RV-300.



Special hardened crownwheels, pinions and drive-line between the rotors allows extreme loading and minimal wear.



The rake is narrowed into transport position on the road and is trailed behind the tractor in the field.

Technical data:	RV-300	RV-390
Working width maximum up to	3,0 m / 9'10"	3,9 m / 12'10"
Tine to tine width raking	2,75 m / 9'	3,6 m / 11'10"
spreading	2,9 m / 9'6"	3,75 m / 12'4"
Transport width	2,5 m / 8'32"	3,2 m / 10'6"
Working speed	10-15 km/hr/6-9 mph	10-15 km/hr/6-9 mph
Output	3-4 ha/hr/7,5-10 acres/hr	4-5 ha/hr/10-12,5 acres/hr
Power requirement	22 KW / 30hp	30 KW / 40hp
Number of tines	20 pcs double	28 pcs double
Tyre	2 pcs 15x6.00-6 4 ply (optional 4 pcs)	4 pcs 15x6.00-6 4 ply
Pto	400-540 rpm	400-540 rpm
Weight	357 kg / 787 lbs	489 kg / 1,078 lbs

Fransgård also offers



Combi rake TI-6000

Importer/Distributor

Dealer

Manufactured by

Fransgård Maskinfabrik A/S
 Fredbjergvej 132, DK-9640 Farsø
 Tel. +45 98 63 21 22
 www.fransgard.dk