

## Dropside Trailers

3 Tonne 18" Dropside Trailer



3 Tonne 18" Dropside Trailer



3 Tonne 18" Dropside Trailer



4 Tonne 18" Dropside Trailer



6½ Tonne 18" Dropside Trailer



7 Tonne 18" Dropside Trailer with sprung axles and optional 380/55 x 17 tyres

The AW Dropside Trailers are fitted with removable drop sides and tailboard, with the headboard being permanently fixed for added strength. They have a strong wide chassis built from PFC or RHS and are fitted with high specification running gear. The tandem axle models can be fitted with either sprung or bogie suspension. There are 3 Tonne, 4 Tonne, 5 Tonne, 6½ Tonne, 7 Tonne, 8 Tonne and 10 Tonne models available.

### Standard Dropside Trailer Features :-

- Hydraulic Tipping
- Hydraulic Brakes
- Commercial Ratchet type Park Brake
- Full Road Lighting
- Rope Hooks
- Fixed Headboard

### Optional Extras Available include :-

- 3 way Tipping Kit
- Mesh Extension Sides
- Screw Jack
- Various tyre upgrades
- Sprung drawbar (on 10 Tonne only)

## Dropside Trailer Optional Extras



### Mesh Extension Sides

(also showing screw jack in lieu of skid)



### 3-way Tipping Kit



### Mesh Extension Sides

## 3 Tonne to 6½ Tonne Dropside Trailers

(single axle)

	3 Tonne Dropside		4 Tonne Dropside		5 Tonne Dropside		6½ Tonne Dropside	
Body length	2740mm	9'	3200mm	10' 6"	3350mm	11'	3660mm	12'
Body width	1730mm	5' 8"	2000mm	6' 6"	2130mm	7'	2210mm	7' 3"
Side heights	460mm only	18" only	460 or 920mm	18" or 36"	460 or 920mm	18" or 36"	460 or 920mm	18" or 36"
Floor thickness	3mm		3mm		3mm		3mm	
Side thickness	3mm		3mm		3mm		3mm	
Chassis	125 x 65 PFC		125 x 65 PFC		150 x 75 PFC		180 x 75 PFC	
Axle size	60mm 6 stud (single)		60mm 6 stud (single)		60mm 6 stud (single)		80mm 6 stud (single)	
Brake size	250 x 40mm		250 x 40mm		250 x 40mm		300 x 60mm	
Wheel track	1500mm	5'	1700mm	5' 7"	1700mm	5' 7"	1900mm	6' 3"
Tyre size	10.00/75 x 15.3 10 ply		10.00/75 x 15.3 10 ply		11.5/80 x 15.3 10 ply		12.5/80 x 15.3 14 ply	
Cubic capacity 460mm	2.2m <sup>3</sup>	78ft <sup>3</sup>	2.95m <sup>3</sup>	102ft <sup>3</sup>	3.28m <sup>3</sup>	115ft <sup>3</sup>	3.72m <sup>3</sup>	135ft <sup>3</sup>
“ “ 920mm	n/a	n/a	5.90m <sup>3</sup>	205ft <sup>3</sup>	6.56m <sup>3</sup>	231ft <sup>3</sup>	7.44m <sup>3</sup>	270ft <sup>3</sup>
o/a length	3950mm	13'	4400mm	14' 5"	4770mm	15' 8"	5080mm	16' 8"
o/a width	1830mm	6'	2070mm	6' 10"	2130mm	7'	2210mm	7' 6"
o/a height (460mm)	1300mm	4' 3"	1300mm	4' 3"	1360mm	4' 6"	1405mm	4' 7"
Bed height	840mm	2' 9"	840mm	2' 9"	900mm	2' 11"	945mm	3' 1"
Unladen weight	0.9 Tonne approx		1.1 Tonne approx		1.2 Tonne approx		1.35 Tonne approx	

## 7 Tonne to 10 Tonne Dropside Trailers

(tandem axle)

	7 Tonne Dropside		8 Tonne Dropside		10 Tonne Dropside	
Body length	3660mm	12'	4300mm	14'	4710mm	15' 6"
Body width	2210mm	7' 3"	2440mm	8'	2440mm	8'
Side heights	460 or 920 mm	18" or 36"	460 or 920mm	18" or 36"	460 or 920mm	18" or 36"
Floor thickness	3mm		3mm		3mm	
Side thickness	3mm		3mm		3mm	
Chassis	180 x 75 PFC		250 x 150 RHS		250 x 150 RHS	
Axle size	70mm 6 stud (tandem)		70mm 6 stud (tandem)		80mm 8 stud (tandem)	
Brake size	300 x 60mm		300 x 60mm		350 x 60mm	
Wheel track	1900mm	6' 3"	2000mm	6' 6¾"	2000mm	6' 6¾"
Tyre size	11.5/80 x 15.3 10 ply		12.5/80 x 15.3 14 ply		385/65R22.5 'super single'	
Cubic capacity 460mm	3.72m <sup>3</sup>	135ft <sup>3</sup>	4.83m <sup>3</sup>	168ft <sup>3</sup>	5.29m <sup>3</sup>	186ft <sup>3</sup>
“ “ 920mm	7.44m <sup>3</sup>	270ft <sup>3</sup>	9.65m <sup>3</sup>	336ft <sup>3</sup>	10.57m <sup>3</sup>	372ft <sup>3</sup>
o/a length	5080mm	16' 8"	5800mm	19'	6250mm	20' 6"
o/a width	2210mm	7' 6"	2440mm	8'	1665mm	5' 6"
o/a height (460mm)	1490mm	4' 11"	1590mm	5' 3"	2125mm	7'
Bed height	1030mm	3' 5"	1130mm	3' 9"	1205mm	4'
Unladen weight	1.55 Tonne approx		1.75 Tonne approx		2.20 Tonne approx	