

# FARM I<sup>®</sup>

## FOREST



Reliable skidding winch engineering with over 45-years experience



290



351P



501

- The automatic over-running brake device guarantees a very smooth pull-out of the cable and prevents run on
- A high pivoted cable entry guarantees optimum spooling into the cable drum
- Decades experience in all weather conditions

FARMI 290 (with 2.9 t pull) and 351P (with 3.5 t pull) are ideal cable winch for small tractors from 15 HP on. Standard model includes the upper cable pulley and ample butt plate with notched beam. The winch comes with the option of a lower guide-pulley.

FARMI 501 winch (with 5 t pull for tractors from 35 HP on) is manufactured with an integrated butt plate and a vertically adjustable lower cable pulley: a light, stable and reliable winch.



Power shaft in the center line of the winch

## FARMI Skidding winches: Technical information

	290	351P	501
Pulling force, max. ton	2,9	3,5	5,0
Cable capacity	ø 8 mm, 80 m ø 10 mm, 55 m	ø 8 mm, 90 m ø 10 mm, 60 m	ø 8 mm, 100 m ø 10 mm, 80 m ø 12 mm, 60 m
Feed-in speed	350 rpm, m/s 540 rpm, m/s	0,2 - 1,0	0,3 - 0,9 0,5 - 1,4
Mechanical plate coupling	yes	yes	yes
Required power, min. hp	from 15	from 15	from 35
Automatic drum brake	yes	yes	yes
Weight without the cable, kg	150	170	250
Three-point mounting	Cat. I	Cat. I and Cat. II	Cat. II
Dozer blade and notched beam	yes	yes	yes
Protective screen	option	option	option
Lower guide pulley	no	option	yes
Holders for along chains	yes	yes	yes
Tool box	no	no	yes

We reserve the right to make changes.

29-501EN /05/2011



Farmi Forest Corporation  
 Ahmolantie 6  
 FI-74510 Iisalmi  
 FINLAND  
 Tel. +358 17 832 41  
 Fax +358 17 382 4372  
 info@farmiforest.fi

For more information and availability, please call

**Davies Implements Ltd**

**Tel.: 01267 237726**

[sales@daviesimplements.co.uk](mailto:sales@daviesimplements.co.uk)