



Low loader / Plant trailer



Model Low Loader

20FT - 16Ton

22ft - 19Ton

Permissible Total Weight	16,000kg	19,000kg
Carrying Capacity	13,000kg	15,500kg
Unladen Weight 3	3,000kg	3,500kg
Width of Bed (mm)	2500	2500
Length of Flat Bed (mm)	4750	5180
Length of Beavertail (mm)	1620	1525
Ramp – Length / Width (mm)	1600 / 800	1800/600
Floor	50mm Kiln Dried Soft Wood Floor	50mm Kiln Dried Soft Wood Floor
Wheel Track Width (mm)	1850	1850
No. Of Axles	2 x 8 Stud	2 x 8 Stud
Axle Manufacturer	ADR/FAD	ADR/FAD
Axle Load	8,000kg	9,000kg
Maximum Hitch Load	3,500kg	3,500kg
Braking System	Hydraulic All Wheel Braking	Hydraulic All Wheel Braking
Braking Size (mm)	300 x 60	300 x 90
Axle Suspension	Hi-Roc 5 Leaf Spring	Hi-Roc 5 Leaf Spring
Tyre Dimensions	215/75 17.5 New J Rated	215/75 17.5 New J Rated
Maximum Speed	50 KPH	50 KPH
Drawbar Towing Eye	Heavy Duty 50mm Fixed Ring	Heavy Duty 50mm Fixed Ring
Lights	LED	LED
	Sprung ramps, fully sheeted	Sprung ramps, fully sheeted
	Sprung drawbar	Sprung drawbar



Davies
Implements Limited

Blaenteg, Trevaughan, Carmarthen SA31 3QN

Tel.: 01267 237726 Email: sales@daviesimplements.co.uk

Website: www.daviesimplements.co.uk