



Hydraulic Cone Splitter

Ideal and compact method of splitting down both good timber and difficult timber such as roots etc.

Can be fitted to a range of machines that can access the timber such as excavators (currently up to 13T) Backhoe's, tele handlers and some heavy duty cranes

Price includes hitch to fit the excavator and 2 x 3/4 hydraulic hoses (2m long)

<u>Model AH500CS</u>	<u>Model AH630CS</u>	<u>Model AH800CS</u>
Excavator 1.5 – 3.5T	Excavator 3 – 6T	Excavator 6 – 14T
Weight 165Kg (excl. hitch)	Weight 170Kg (excl. hitch)	Weight 185Kg (excl. hitch)
Cone 200 Dia x 400 long Removable hardened tip	Cone 200 Dia x 400 long Removable hardened tip	Cone 250 Dia x 400 long Removable hardened tip
Hydraulic Motor Max torque 2123 N/m	Hydraulic Motor Max torque 2338 N/m	Hydraulic Motor Max torque 2475 N/m
Price (incl. hitch & hoses)	Price (incl. hitch & hoses)	Price (incl. hitch & hoses)
Opt Extra Dual X line R/V to control any over pressure from machine system	Opt Extra Dual X line R/V to control any over pressure from machine system	Opt Extra Dual X line R/V to control any over pressure from machine system
Max log size (typical) 2 Mt long x 1 Mtr Dia.	Max log size (typical) 2 Mt long x 1.1 Mtr Dia.	Max log size (typical) 3 Mt long x 1.3 Mtr Dia.
£ POA	£3,600 Plus VAT	£4,000 plus VAT