

MITSUBISHI TRACTOR

WWW.MSTRACTORS.COM

Compact 'Off Road'
MITSUBISHI TRACTORS





SPEC of MTU26
Model : MTU26 HST

std.standard NA-not available
opt: option NS:(MAM)not supply

[ENGINE]		
Model		S3L2
Type		Water cooled Diesel
Injection type		I.D.I.
Engine Horsepower(gross)	HP	24.7
Engine Maximum Horsepower(gross)	HP	25.9
Engine Horsepower(net)	HP	-
PTO Horsepower	HP	18.5
Rated Engine Speed	rpm	2500
Number og Cylinders		3
Total Displacement	in^3(cc)	80.4(1318)
Bore x Stroke	in(mm)	3.07x3.62(78x92)
Oil filter		Catridge
Air filter		Dual Dry
Capacities Fuel Tank	USgal(L)	7.1(27)
Coolant reserve tank		std
Alternator	A	50
[DIMENSIONS]		
		AG Tires
		7-16/11.2-24
Overall Length with 3-PH	in(mm)	121.2(3080)
Overall (min.tread)	in(mm)	55.1(1400)
Height to Top of ROPS (Rear ROPS)	in(mm)	94.1(2391)
(Front ROPS)	in(mm)	86.9(2208)
Wheelbase	in(mm)	67.3(1710)
Min. Ground Clearance	in(mm)	13.0(330)
Tread Front (STD)	in(mm)	42.8(1087)
Tread Rear (STD)	in(mm)	42.9(1090)
Turning Radius W/Break	feet(m)	7.9(2.4)
Weight(Rear ROPS) Total	lbs(kgf)	2599(1175)
(at full Fuel) Front	lbs(kgf)	1100(499)
Rear	lbs(kgf)	1501(681)
Weight(Front ROPS) Total	lbs(kgf)	2643(1208)
(at full Fuel) Front	lbs(kgf)	1111(525)
Rear	lbs(kgf)	1523(691)
[DRIVE-TRAIN]		
Gear Transmission Type A		-
Number of Speeds		-
Shuttle (Forward &		-
Revers)		-
Gear Transmission Type B		-
Number of Speeds		-
HST		HST
Number of Speeds		3 Range
Cruise control		STD
Speed Forward speed	km/h	0-20.8(at 11.2-24)
Creep Speed (Gear)		N.A.
Breakes Type		Wet-Disc
Park brake		Hand brake
Clutch Type		Dry - Single
4WD		std
Inter-axle Ration (front/rear)		1.590

[PTO Type]		
Rear PTO Seed	rpm	540@2376
	rpm	NA
Type		Live with o/r clutch
Shaft size		1-3/8
Mid PTO Speed	rpm	2000(Option)@2525
Type		Live
Shaft size		SAE 1"-15teeth
Optional Type		
[HYDRAULIC SYSTEM]		
Pump		Dual-Gear type
implement Pump Cap.	gal/min	7.5(28.5)
Maximum pressure	psi(kg/cm^2)	2205(9155)
Steering pump Cap.	gal/min	3.3(12.2)
Maximum pressure	psi(kg/cm^2)	1494(105)
Lift Capacity at ball-end	lbs(kg)	2646(1200)
Lift Capacity at 24" behind	lbs(kg)	1720(780)
Lift Control Type Std		Position
Option		
Auxilialy valve		Opt.(1)
Hydraulic outlet block		std(side of chassis)
[3P Linkage]		
Hitch category		1
telescopic stabilizers		std
Righ lift rod adjustment		Turn Buckle
[CAPACITIES]		
Cooling System	gal(L)	1.5(5.5)
Coolant bottle	gal(L)	0.09(0.33)
Crankcase	gal(L)	1.1(4.2)
Transmission & Hyd.	gal(L)	9.0(34)
Front Axle	gal(L)	1.1(4.0)
[Operation]		
Deck type		Semi Flat Deck
Pedal type		Floor Mount
Seat		KAB(XH2/P1)
Steering System		Hyd. P/S
Tilt Steering wheel		Std (3 positions)
Foldable ROPS		Rear mount
		Mid mount(Opt)
[TIRE SIZE AG] (LOCAL PROCUREMENT)		
AG Tires (Front/Rear)		7-14/9.5-24
		7-16/11.25-24
Turf Tires (Front/Rear)		25x8.50-14/13.6-16
		212/80D15/355/80D20
[IMPLEMENT]		
Allowable Load Total	lbs(kg)	5070(2300)
Allowable Load Front Axle	lbs(kg)	3086(1400)
Rear Axle	lbs(kg)	3086(1400)

[ELECTRICAL SYSTEM]		
Battery		12V-490CCA(55AH)
Panel		std
Fuel meter		std
Hour & Tacho meter		std
Coolant temp. meter		std
Battery change lamp		std
Engine oil pressure lamp		std
Parking break indicator		std
Elec. Key shutoff		std
Electrical horn		std
Head lamp		std
Front position lamp		std
Rear position lamp		std
Turn signal lamp (hazard)		std
License plate lamp		std
Stop lamp		std
Rear red reflector		std
Rear work lamp		N.S.
Engine glow system		std
7-pin connector		N.S.
rear view mirror		std
[OTHERS]		
Engine hand throttle		std
Engine foot throttle		N.A.
Muffler		Inner side cover
Seat		KAB(XH2/P1)
Suspension seat		std
Rops w/seat belt		std
Tool		N.S.
Tool Box		N.A.
License plate bracket		std
[GRAND SPEED]		
F-1 / R-1	km/h	L Range
2 / 2		0-4.6/0-2.3
3 / 3		3.1/2.7
4 / 4		M Range
5 / 5		0-8.3/0-4.1
6 / 6		7.8/6.5
7 / 7		H Range
8 / 8		0-19.2/0-9.6
9		
max / max		0-20.8/0-10.3

STRONGER

780 Kg lifting capacity with 2 PTO speeds of 540 and 1000.

POWERFULL

26 hp genuine Mitsubishi latest tier 5 engine with heavy duty chassis.

FASTER

24 KPH.

MANEUVERABILITY

Amazing turning circle 2.4m

USER FRIENDLY

Hydrostatic Transmission - no gear changing required.

DURABLE

All made in Japan.


RELIABLE

Mitsubishi Tractor factory 3 years warranty.

CHOICE

A choce of Agricultural or Turf tyres available.





MITSUBISHI TRACTOR

WWW.MSTRACTORS.COM

0121 740 0194

