

# Teagle

# Topper 8 Offset



● 8' Cut

● Heavy Swinging Blades

● Rugged and Simple

● Spring Steel Rotors

**The Offset Topper** is designed for general agricultural use where there is a specific requirement to avoid wheelmarks. Power requirement is 60kW (80HP).

**A Perfect Finish** is provided by the fully overlapping twin rotors – no possibility of an uncut central strip.

**Hydraulic Folding & Breakaway** for full protection and control from the tractor seat. There is no need to disconnect shafts for transport. Mechanical locking is provided to retain the machine in the transport position.



# **Teagle** Topper 8 Offset

## **Strong, Simple Construction**

incorporating foldings and pressings for rigidity. Also assists the smooth flow of cut material through the machine.

## **Hardened Spring Steel Blades**

Pivot on hardened bushes. The blades are cranked to reduce any possibility of stone damage.

**Drive** is through a heavy duty bevel gearboxes and shafts incorporating flexible couplings to minimise shock loads. Shear bolt protection is included in the PTO shaft.



**Pivoting Suspension** system allows the Offset Topper to float over ground undulations. Spring cushioning is provided.

**Cutting Height** is variable between 1/2" - 4" (12mm - 100mm) by means of adjustable skids.

**Good Spreading** of cut material is provided by underbody dividers and deflectors. The blades are designed to give good turbulence.



## **Specifications**

Cutting Width	8' 0" (2.4m)
Transport Width	5'11" (1.8m)
Transport Length	11'5" (3.5m)
Cutting Height	1/2" - 4" (12mm - 100mm)
Linkage	Category 2
Weight	1180lb (535kg)

Your local dealer is:-

The Company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice

# **Teagle**

Manufactured by: **Teagle Machinery Limited**,

Blackwater, Truro, Cornwall, TR4 8HQ  
Tel: 01872 560592 Fax: 01872 561166  
e-mail: sales@teagle.co.uk  
Web: www.teagle.co.uk