




uper compact saw bench for private use!

- 600 or 700 mm dia. steel or widia blade at choice, with 30 mm dia. hole.
- Standard cutting control manually operated.
- Transmission with Poly V flat belt .
- Exceptional performance also for 700 mm dia. blade model with 230 Volt motor thanks to the flywheel supplied as standard mounted on the motor.
- Electric motors in class S2 as standard.
- Safe-to-use, easy to handle and to store after work.




SWING TANK SAW BENCH for max. 28 cm dia. cut







Cutting length adjustment. Included.



Model	Katana 600	Katana 700	Katana 700	Katana 700
Widia blade , 30 mm dia. hole and blade diameter (mm) <u>included</u>	ø 600 DW.600.30	ø 700 dw.700.30	ø 700 DW.700.30	ø 700 dw.700.30
Power supply EL = electric, V.PF = tractor	EL 230 Volt	EL 230 Volt	EL 400 Volt	V.PF 450 rpm
Power required (HP / kW)	3 / 2.2	3 / 2.2	5 / 3.7	11/8
Max. dia. cut (cm)	22	28	28	28
Blade revs (rpm.)	1600	1400	1400	1400
Electrical stopping brake on the blade	•	•	•	
Transport wheels (dia. mm) full	300	300	300	300
3-point connector 1 st – 2 nd cat.				•
Cut adjuster	•	•	•	•
Thrust roller 60 x 120 dia.	optional D.60.120	optional D.60.120	optional D.60.120	optional D.60.120
Flywheel	optional D.280.19	 as standard 	optional D.280.19	
Weight (kg)	115	133	125	122
Shipment dimensions (AxBxH cm)	60x80x120	60x80x120	60x80x120	60x80x120
List price excl. VAT (€)				
Net price excl. VAT (€)				
= delivery time: 4 weeks	0		0	
Code	RR.60.223.W	RR.70.223.W	RR.70.384.W	RR.70.V.PF.W



OPTIONAL ACCESSORIES							
Description	Steel blade		Widia blade		Flywheel	Roller	Cardan shaft
Code	DA.600.30	DA.700.30	DW.600.30	DW.700.30	D.280.19	D.60.120	600.059